



## 85150 – Swing Axle Honda Hitch

Description	Quantity
Honda Receiver Hitch	1
1/2" U-Bolt	1
1/2" Nylock Nut	2
1/2" Flat Washer	2
3/4" x 1 1/2" Hex Bolt	1
3/4" Flat Washer	2
3/4" Lock Washer	1
5/8" x 3" Bent Hitch Pin	1
R-Pin	1
Manual	1



### Hitch Mounting:

1. Place receiver hitch as shown above over the frame of the ATV rear suspension.
2. U-Bolt from under the frame and through the Hitch Plate.
3. Attach using the 1/2" Washers and Nuts provided. (See Above Photo)
4. Using 3/4" Hex Bolt, insert 3/4" lock washer and 3/4" flat washer onto bolt and insert through the existing hitch and thread into Kolpin DirtWorks Honda Receiver Hitch.

### Hitch Use:

- The 2" Receiver hitch is designed to allow you to quickly and easily mount and dismount the DirtWorks 3-Point Hitch system.
- Kolpin recommends the use of the Universal Swing Arm Suspension Lock with the use of the DirtWorks System.
- The hitch can also be used for chores around the house, such as moving your boats, trailers, etc.

**\*Do not exceed the Manufactures Recommended Hitch Capacity\***

### Hitch Compatible With:

1. TRX 500 FA Rubicon 4x4 - 04 & Older
2. TRX 400 S Foreman 4x4 - 04 & Older
3. TRX 400 Automatic 4x4 – 2004
4. TRX 500 Foreman 4x4 – 2005

Kolpin Outdoors, Inc.  
205 N. Depot Street, Fox Lake, WI 53933  
Phone #: (877) 9KOLPIN or (920) 928-3118  
www.kolpin.com  
customerservice@kolpin.com